

Application No. 10/706,947  
Amendment dated September 6, 2007  
Reply to Office Action dated March 7, 2007

**AMENDMENTS TO THE CLAIMS:**

1. (currently amended) A disengageable connector for interconnecting panels, the connector comprising;

a longitudinally extending connector body having a substantially similar profile along its entire length, the connector body including a base and a projection extending from the base;

the base includes a top surface and a bottom surface, and ~~at least one a first~~ first footing member extending downwardly from the bottom surface of the base, a second footing member extending downwardly from the bottom surface of the base and a third footing member extending downwardly from the bottom surface of the base, the footing member being shaped and dimensioned to compress the upper surface of a resilient pad positioned beneath the connector and the panels; and

a first protrusion extending vertically from the base adjacent a first edge of the base and a second protrusion extending vertically from the base adjacent a second edge, opposite the first edge, of the base, the first protrusion and the second protrusion are spaced apart from the projection and are located on either side of the projection;

wherein the first footing member and the second footing members are respectively positioned beneath the first protrusion and the second protrusion, and the third footing member is positioned beneath the projection, and the first footing member, the second footing member and the third footing member are shaped and dimensioned to compress into an underlying foam pad to a predetermined limited extent such that the connector sits upon the underlying foam pad with the

Application No. 10/706,947  
Amendment dated September 6, 2007  
Reply to Office Action dated March 7, 2007

top surface of the base lying in substantially the same plane as the upper surface of the underlying foam pad.

2. (original) The connector according to claim 1, wherein the projection extends vertically from the top surface of the base, the projection having top and bottom portions, and comprising right and left halves for insertion into edges of adjacent panels to be connected.

3. (canceled)

4. (currently amended) The connector according to claim ~~[[3]]~~ 1, wherein the ~~base includes~~ first, ~~and second~~ and third footing members are respectively approximately 0.036 inches in depth~~positioned beneath the protrusions.~~

5. (original) The connector according to claim 4, wherein the protrusions extend substantially the entire length of the connector.

6. (original) The connector according to claim 4, further including a third footing member positioned beneath the projection.

7. (original) The connector according to claim 6, wherein a recess is formed between the first footing member and the third footing member and a recess is formed between the second footing member and the third footing member.
8. (withdrawn) An interlocking flooring system, comprising:
  - a plurality of flooring panels, each flooring panel including a plurality of edges;
  - a first connecting member for connecting adjacent flooring panels and a second connecting member for connecting adjacent flooring panels, the first connecting member being different from the second connecting member and providing greater resistance to disengagement of adjacent flooring panels when compared to the second connecting member; and
  - a resilient pad positioned beneath the flooring panels.
9. (withdrawn) The interlocking flooring system according to claim 8, wherein each flooring panel includes at least one short edge and at least one long edge, and the first connecting member is shaped and dimensioned for coupling the at least one short edge to an adjacent flooring panel and the second connecting member is shaped and dimensioned for coupling the at least one long edge to an adjacent flooring panel.
10. (withdrawn) The interlocking flooring system according to claim 8, wherein the first connecting member includes a longitudinally extending connector body, the connector body including a base and a projection extending from the base; the base includes a top surface and a

bottom surface, and at least one footing member extending downwardly from the bottom surface of the footing member, the footing member being shaped and dimensioned to compress the upper surface of the resilient pad positioned beneath the connector and flooring panels.

11. (withdrawn) The interlocking flooring system according to claim 10, wherein the second connecting member includes a longitudinally extending connector body, the connector body including a base and a projection extending from the base; the base includes a top surface and a bottom surface.

12. (withdrawn) The interlocking flooring system according to claim 10, wherein the second connecting member includes a tongue extending from an edge of a flooring panel and a groove extending from an edge of an adjacent flooring panel.

13. (withdrawn) The interlocking flooring system according to claim 10, wherein the first connecting member includes two protrusions extending vertically from the base, the protrusions are spaced apart from the projection and are located on either side of the projection beyond a lateral extent of the extensions; and the second connecting member includes two protrusions extending vertically from the base, the protrusions are spaced apart from the projection and are located on either side of the projection beyond a lateral extent of the extensions .

Application No. 10/706,947  
Amendment dated September 6, 2007  
Reply to Office Action dated March 7, 2007

14. (withdrawn) The interlocking flooring system according to claim 13, wherein the at least one footing member includes first and second footing members respectively positioned beneath the protrusions.

15. (withdrawn) The interlocking flooring system according to claim 14, further including a third footing member positioned beneath the projection.

16. (currently amended) A disengageable connector for interconnecting panels, the connector comprising;

a longitudinally extending connector body, the connector body including a base having a longitudinal extent with a first end and a second end, the connector further including a projection extending vertically from a top surface of the base;

a first protrusions extending vertically from the base adjacent a first edge of the base along an entire length of the base and a second protrusions extending vertically from the base adjacent a second edge, opposite the first edge, of the base along the entire length of the base; and

wherein the projection extends beyond the longitudinal extent of the base along at least one end of the base to define an outwardly extending ear.

17. (original) The connector according to claim 16, wherein the projection includes a top portion and a bottom portion, the projection further including right and left halves for insertion into edges of adjacent panels to be connected.

Application No. 10/706,947  
Amendment dated September 6, 2007  
Reply to Office Action dated March 7, 2007

18. (currently amended) The connector according to claim 16, wherein the base includes a bottom surface and ~~at least one~~ longitudinally extending first and second footing members ~~extends~~ extending downwardly from the bottom surface of the base and in the same direction as the base, the first and second footing members being shaped and dimensioned to compress the upper surface of a resilient pad positioned beneath the connector and flooring panels, wherein the first and second footing member are respectively positioned beneath the first protrusion and the second protrusion.

19. (canceled)

20. (currently amended) The connector according to claim ~~[[19]]~~ 16, wherein each of the first protrusion and the second protrusion extends beyond the longitudinal extent of the base along at least one end of the base to form a locking tab.

21. (withdrawn) An interlocking flooring system, comprising:

a plurality of flooring panels, each flooring panel includes first and second long edges and first and second short edges, each flooring panel also including first and second grooves in an underside of the flooring panel respectively adjacent the first and second short edges;

the first and second long edges respectively include integral connecting members shaped and dimensioned such that the connecting member of the first long edge will engage the connecting member of the second long edge of an adjacent flooring panel;

Application No. 10/706,947  
Amendment dated September 6, 2007  
Reply to Office Action dated March 7, 2007

a distinct connector shaped and dimensioned for coupling the first or second short edges of adjacent flooring panels, the connector includes a longitudinally extending connector body, the connector body including a base and a projection extending from the base; the base includes a top surface and a bottom surface, the base further includes two protrusions extending vertically from the top surface, the protrusions being spaced apart from the projection and being located on either side of the projection in a position to grip the first and second grooves formed along the underside of the flooring panels.

22. (withdrawn) The flooring system according to claim 21, wherein the connector includes at least one footing member extending downwardly from the bottom surface of the footing member, the footing member being shaped and dimensioned to compress an upper surface of a resilient pad positioned beneath the connector and flooring panels.

23. (withdrawn) The flooring system according to claim 22, wherein the base includes first and second footing members respectively positioned beneath the protrusions.

24. (withdrawn) The flooring system according to claim 23, further including a third footing member positioned beneath the projection.

Application No. 10/706,947  
Amendment dated September 6, 2007  
Reply to Office Action dated March 7, 2007

25. (withdrawn) The flooring system according to claim 21, wherein the flooring panels include a backing layer along the underside and the first and second grooves are cut into the backing layer such that the protrusions grip the backing layer.

26. (withdrawn) The flooring system according to claim 21, further including a resilient pad positioned beneath the flooring panels.